

Hydraulic Lift **HPT**



INTRODUCTION

Hydraulic Lift is fully to be customized, usually applied in industrial & mining factories, medicine industry, logistics industry and all sorts of production lines to facilitate goods handling works. The hydraulic system follows the designs of anti-explosion to enhance its operation safety. The machine is of manganese steel structure with huge load capacity. Its exact specification is as per customer's different requirements. The control option includes up-down control, ground control, and multi control.

Application:

*Elevating or unloading goods between basements and stories, elevating stages / operation tables, etc.

Features:

Huge load capacity, nice figure, simple structure, little breakdown and easy operation & maintenance



Safety protection: range limit switch



Optional stopper on the platform



Optional pedal control for lifting and lowering



Quality guaranteed hydraulic unit

REF. PICTURES



1. The platform of a hydraulic lift can be optional, eight motorized / gravity conveyors (roller & belt) or just steel plate.

2. The scissors of a hydraulic lift is also optional as per different load capacity and lifting height. Multi-scissors guarantee the stability & safety.

3. Customized hydraulic lift can be equipped with wheels to move around easily.

4. Simple structured light duty hydraulic lifts are available for storehouse uses.

TECHNICAL PARAMETERS

ITEMS	OPTIONS
Lift Platform	Steel plate, Gravity rollers, Motorized rollers, Belt, etc
Scissors Form	Single scissors, double scissors, single multi-scissors, double multi-scissors
Platform Size	Optional, as per specific purposes
Height Range	Optional, both for folded height and lifted height
Lifting Time	Optional, as per specific need
Capactiy	Optional, usually 1000-3000kgs
Control Options	Manual control box, Pedal control, Multi control, etc

P.S.: *Hydraulic Lift (HPT) can be fully customized as per specific requirements.



MHE CONVEYOR INDUSTRY CO., LTD.
NINGBO MEWHE IMPORT & EXPORT CO., LTD.
 NO. 252 XINGYONG RD, YONGJIANG INDUSTRY
 ZONE, JIANGBEI 315000, NINGBO, CHINA
 TEL: 86 574 6229 2607 FAX: 86 574 6257 8059
 MOB (24H): 86 133 0663 8833
 EMAIL: CONVEYOR@NBMHE.COM
 WEB: WWW.CONVEYOREXPERT.COM

Hydraulic Stacker HDG-1000, 1500, 2000



INTRODUCTION

Hydraulic Stacker is semi-automatic stacker, helping to facilitate stacking work. The steel framework is of good rigidity and high strength, which make the stacker durable in use. The light and flexible structure guarantees a small turning radius and pleasant operation. The standard fork width allows itself to stack international pallets with ease.

TECHNICAL PARAMETERS

ITEMS	OPTIONS	ITEMS	OPTIONS
Capacity	Optional, usually 1000kg, 1500kg, 2000kg, etc	Fork Lift Height	90mm-max.1550mm
Fork Size	Spread: max. 980mm; Length: 900mm; Load center: 500mm	Wheel Material	Nylon, Poly, Rubber, etc
Turning Wheel Dia.	150mm	Overall Size	L1400mm * W1000mm * H2050mm



MHE CONVEYOR INDUSTRY CO., LTD.
NINGBO MEWHE IMPORT & EXPORT CO., LTD.
 NO. 252 XINGYONG RD, YONGJIANG INDUSTRY ZONE, JIANGBEI 315000, NINGBO, CHINA
 TEL: 86 574 6229 2607 FAX: 86 574 6257 8059
 MOB (24H): 86 133 0663 8833
 EMAIL: CONVEYOR@NBMHE.COM
 WEB: WWW.CONVEYOREXPERT.COM

Pallet Jack / Truck HTP-1500, 2000, 2500, 3000



INTRODUCTION

Pallet Truck is economically designed, of light steel structure coated with standard epoxy to avoid fragmentation and corrosion. The welding point and reinforced fork top are durable in use. The reliable hydraulic system effectively avoids oil leaking and the oil pump can reach up to 12 strokes, with 11mm higher per stroke.

Application:

*Pallet moving work in logistics industry and places like warehouse, dock, supermarket, etc.

Features:

Simple structure, little breakdown and easy operation & maintenance, durable

TECHNICAL PARAMETERS

ITEMS	OPTIONS	ITEMS	OPTIONS
Capacity	Optional, usually 1500kg, 2000kg, 2500kg, 3000kg, etc	Fork Lift Height	85mm-200mm, 75mm-190mm
Fork Size	Spread: 550mm, 685mm, etc Length: 1150mm, 1220mm	Wheel Material	Nylon, Poly, Rubber, etc
20' GP Load	180pcs for 550mm fork type, 144pcs for 685mm fork type	40' HQ Load	318pcs for 550mm fork type, 288pcs for 685mm fork type